



## Colortone

Available in Dune eVo, Fine Fissured or Neeva surfaces depending on your acoustic requirements, the Colortone Range offers a simple way to add darker tones and more depth to your ceilings. Combine the black colour option with Prelude 24 black grid for the perfect solution for cinema applications and other dark spaces.


# Colortone Neeva

## Key Features

- Excellent acoustical absorption:  $1.00 \alpha_w$
- Available in Black
- Ideal cafeterias, cinemas and theatres



## Edge Detail Board




**Thickness (mm)** 15

**Modules (mm)** 600 x 600 ..... 2695DBK  
1200 x 600 ..... 2696MBK


**Suspension Systems** Prelude 24 XL<sup>2</sup> / TLS  
RAL 9005


**Colour** Black (BK)

**Sustainability**




20






EN 13964 / E1


**Acoustics**



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1



EN ISO 140-3  
& EN ISO 717-1


	Hz $\alpha_p$										
	$\alpha_w$	$D_{nfw}$	$R_w$	Class	NRC	125	250	500	1000	2000	4000
Board	1.00	–	7 dB	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00

**Fire Reaction**





**EEA Euroclass A1**  
EN 13501-1

**Performances & Features**




95% RH






30 Year System Guarantee



1.2 Kg/m<sup>2</sup>



BIM READY


If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 073.1.10.22

# Colortone Dune eVo

## Key Features

- 3 edge details available
- Available in Platinum
- Ideal cafeterias, cinemas and theatres



Edge Detail	Board	Tegular	MicroLook 90
Thickness (mm)	15	15	15
Modules (mm)	600 x 600 ..... 5460MPN 1200 x 600 ..... 5461MPN	600 x 600 ..... 5462MPN	600 x 600 ..... 5464MPN
Suspension Systems	Prelude 24 XL <sup>2</sup> / TLS	Prelude 24 XL <sup>2</sup> / TLS	Prelude 15 TL / TLS
Colour	Platinum (PN)		

## Sustainability



44



A



EN 13964 / E1

## Acoustics



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1

	$\alpha_w$	$D_{nfw}$	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular, MicroLook 90	0.60(H)	34 dB	C	0.50	0.40	0.40	0.60	0.55	0.55	0.50

## Fire Reaction



EEA Euroclass A2-s1, d0  
EN 13501-1

## Performances & Features



Up to 72%



95% RH



30 Year System Guarantee



3.6 Kg/m<sup>2</sup>



BIM READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)