



Optima

Optima has a fine textured surface and offers Class A sound absorption finish with fibre scrim.

Key Features

- Excellent sound absorption: up to 1.00 α_w
- High light reflectance: 87%
- Excellent mechanical strength (fibre glass fleece at the back)
- Ideal for open spaces, call centres and libraries



Edge Detail	Board	Tegular24	Tegular15	Integra
Thickness (mm)	15 / 20	15 / 20	15 / 20	22
Modules (mm)	600 x 600 x 15...2327M 1200 x 600 x 15...2328M 600 x 600 x 20...2335M	600 x 600 x 15...2329M 600 x 600 x 20...2349M	600 x 600 x 15...2331M 600 x 600 x 20...2363M	600 x 600...2387M 1200 x 600...3413M
Suspension Systems	Gridline 24 Butt Cut/ Joggled Prelude 24 Sixty ²	Gridline 24 Butt Cut/ Joggled Prelude 4 Sixty ²	Gridline 15 Butt Cut/ Joggled Interlude HRC Silhouette	Gridline 24 Butt Cut/ Joggled Prelude 24 Sixty ²

Colour Global White

Sustainability



77



A



EN 13964 / E1

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

	α_w	D_{nfw}	R_w	Class	NRC	Hz α_p						
						125	250	500	1000	2000	4000	
Board, Tegular24, Tegular15 (15mm)	0.90(H)	-	7 dB	A	0.90	0.35	0.75	1.00	0.80	0.90	0.95	
Board, Tegular24, Tegular15 (20mm)	0.95(H)	-	-	A	0.95	0.40	0.80	1.00	0.85	1.00	1.00	
Integra	1.00(H)	-	-	A	0.95	0.35	0.80	1.00	0.90	1.00	1.00	

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



87%



95% RH



1.5 Kg/m² (15mm)
2.0 Kg/m² (20mm)
2.8 Kg/m² (22mm)



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 112.2.03.24