




















Ceramaguard (100% RH)

With its unique high density mineral composition, Ceramaguard is steam resistant and will retain its physical integrity even when subjected to 100% RH. It also features a washable finish and is lightly fissured to provide acoustic performance.

Key Features

- 100% RH resistance
- Durable, washable and scrubbable
- Resistant to growth of mould, mildew and bacteria
- Good balance between sound attenuation and absorption
- Ideal for swimming pools, locker rooms, shower areas and indoor parking areas



Edge Detail	Board										
Thickness (mm)	15										
Modules (mm)	600 x 600 607M										
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Corrosive Resistant ¹ Clean Room 24					¹ Ceramaguard must be installed on Prelude 24 Corrosive Resistant grid where humidity regularly exceeds 95% RH. Ceramaguard may need to have Main Runners at 600 mm centres due to increased weight in high humidity conditions.					
Colour	Global White										
Sustainability	 37		 A+	 EN 13964 / E1							
Acoustics	 EN ISO 354 & EN ISO 11654		 EN ISO 10848-2 & EN ISO 717-1								
		α_w	D_{nfw}	Class	NRC	125	250	Hz α_p			
Board		0.55(MH)	–	D	0.60	0.25	0.30	0.50	0.80	0.85	0.75
Fire Reaction	 Euroclass A1 EN 13501-1										
Performances & Features	 79%	 7.3Kg/m ² 20 Kg/m ² > if wet			 30 Year System Guarantee						
	 100% RH			 BIM READY							

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 071.1.09.22