

## SAFETY DATA SHEET

## Sonify Panel Touch Up

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Trade name

Sonify Panel Touch Up

## Product no.

BPATUPP50PA

## Unique formula identifier (UFI)

Q500-C029-G00C-D8X8

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture

Paint application to canopy or baffles.

## Uses advised against

Process category	Description
N/A	Do not apply to grid

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**Zentia Ltd.**

Kingsway South,  
Team Valley,  
NE11 0SP Gateshead,  
United Kingdom  
Reception 0191 497 1000, Customer Service 0191 497 1001

## E-mail

Contact details i.e., general email address - [www.zentia.com](http://www.zentia.com)

## Revision

20/01/2023

## SDS Version

1.0

## 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

## SECTION 2: Hazards identification

## 2.1. Classification of the substance or mixture

Carc. 2; H351, Suspected of causing cancer.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

## 2.2. Label elements

## Hazard pictogram(s)



## Signal word

Warning

## Hazard statement(s)

Suspected of causing cancer. (H351)

May cause damage to organs through prolonged or repeated exposure. (H373)

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

## Safety statement(s)

### General

-

### Prevention

Obtain special instructions before use. (P201)

Do not breathe vapour/mist. (P260)

Wear face protection/protective gloves/protective clothing. (P280)

### Response

IF exposed or concerned: Get medical advice/attention. (P308+P313)

Get medical advice/attention if you feel unwell. (P314)

### Storage

Store locked up. (P405)

### Disposal

Dispose of contents/container in accordance with local regulation. (P501)

## Hazardous substances

Melamine

## Additional labelling

EUH208, Contains reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1).

May produce an allergic reaction.

UFI: Q500-C029-G00C-D8X8

## 2.3. Other hazards

### Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Melamine	CAS No.: 108-78-1 EC No.: 203-615-4 UK-REACH: Index No.:	10-20%	Acute Tox. 4, H312 Carc. 2, H351 STOT RE 2, H373	[5]
(2-methoxymethylethoxy)propanol	CAS No.: 34590-94-8 EC No.: 252-104-2 UK-REACH: Index No.:	1-3%		[1]
2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether	CAS No.: 112-34-5 EC No.: 203-961-6 UK-REACH: Index No.: 603-096-00-8	<1%	Eye Irrit. 2, H319	[1], [3]
2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve	CAS No.: 111-76-2 EC No.: 203-905-0 UK-REACH: Index No.: 603-014-00-0	<1%	Acute Tox. 4, H302 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332	[1]
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	CAS No.: 55965-84-9 EC No.: 611-341-5 UK-REACH: Index No.: 613-167-00-5	<0.1%	EUH071 Acute Tox. 3, H301 Acute Tox. 1, H310 Skin Corr. 1C, H314 (SCL: 0.60 %) Skin Sens. 1A, H317 (SCL: 0.0015 %)	

Eye Dam. 1, H318 (SCL: 0.60 %)  
Acute Tox. 2, H330  
Aquatic Acute 1, H400 (M=100)  
Aquatic Chronic 1, H410 (M=100)

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

- [1] European occupational exposure limit.
- [3] According to UK REACH, Annex XVII, the substance is subject to restrictions.
- [5] Substance is included in the Candidate List of substances of very high concern (SVHC).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

##### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

##### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

##### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

##### Burns

Not applicable.

#### 4.2. Most important symptoms and effects, both acute and delayed

Prolonged inhalation of high concentrations may damage respiratory system.

Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Prolonged contact may cause dryness of the skin. Discoloration of the skin.

#### 4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

##### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

#### Recommended storage material

No specific requirements

#### Storage temperature

Keep in a bonded area. Keep in properly labeled containers. Keep out of the reach of children. Keep locked up or in an area accessible only to qualified or authorized persons. Store between 41 and 77 °F (5 - 25° C) in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

#### Incompatible materials

Strong oxidizing agents

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

(2-methoxymethylethoxy)propanol

Long term exposure limit (8 hours) (ppm): 50

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 308

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether

Long term exposure limit (8 hours) (ppm): 10

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 67,5

Short term exposure limit (15 minutes) (ppm): 15

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 101,2

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Long term exposure limit (8 hours) (ppm): 25  
 Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 123  
 Short term exposure limit (15 minutes) (ppm): 50  
 Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 246

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.  
 EH40/2005 Workplace exposure limits (Fourth Edition 2020).

## DNEL

(2-methoxymethylethoxy)propanol

Duration	Route of exposure	DNEL
Long term – Systemic effects - General population	Dermal	121 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	283 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	37.2 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	308 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	36 mg/kg bw/day

2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether

Duration	Route of exposure	DNEL
Long term – Local effects - Workers	Inhalation	67.5 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	101.2 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6.25 mg/kg bw/day

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve

Duration	Route of exposure	DNEL
Long term – Local effects - General population	Dermal	89 mg/kg
Long term – Systemic effects - General population	Dermal	75 mg/kg
Long term – Systemic effects - Workers	Dermal	125 mg/kg
Short term – Local effects - Workers	Dermal	89 mg/kg
Long term – Local effects - General population	Inhalation	426 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Inhalation	59 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	98 mg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	147 mg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	1091 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	6.3 mg/kg
Short term – Systemic effects - General population	Oral	26.7 mg/kg

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)

Duration	Route of exposure	DNEL
Long term – Local effects - General population	Inhalation	20 µg/m <sup>3</sup>
Long term – Local effects - Workers	Inhalation	20 µg/m <sup>3</sup>
Short term – Local effects - General population	Inhalation	40 µg/m <sup>3</sup>
Short term – Local effects - Workers	Inhalation	40 µg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	90 µg/kgbw/day
Short term – Systemic effects - General population	Oral	110 µg/kgbw/day

## PNEC

(2-methoxymethylethoxy)propanol

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Route of exposure	Duration of Exposure	PNEC
Freshwater		19 mg/L
Freshwater sediment		70.2 mg/kg
Intermittent release (freshwater)		190 mg/L
Marine water		1.9 mg/L
Marine water sediment		7.02 mg/kg
Sewage treatment plant		4.168 g/L
Soil		2.74 mg/kg
<b>2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether</b>		
Route of exposure	Duration of Exposure	PNEC
Freshwater		1.1 mg/L
Freshwater sediment		4.4 mg/kg
Intermittent release (freshwater)		11 mg/L
Marine water		110 µg/L
Marine water sediment		440 µg/kg
Predators		56 mg/kg
Soil		320 µg/kg
<b>2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve</b>		
Route of exposure	Duration of Exposure	PNEC
Freshwater		8.8 mg/L
Freshwater sediment		34.6 mg/kg
Marine water		0.88 mg/L
Marine water sediment		3.46 mg/kg
Sewage treatment plant		463 mg/L
Soil		2.33 mg/kg
<b>reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)</b>		
Route of exposure	Duration of Exposure	PNEC
Freshwater		3.39 µg/L
Freshwater sediment		27 µg/kg
Intermittent release (freshwater)		3.39 µg/L
Intermittent release (marine water)		3.39 µg/L
Marine water		3.39 µg/L
Marine water sediment		27 µg/kg
Sewage treatment plant		230 µg/L
Soil		10 µg/kg

## 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

There are no exposure scenarios implemented for this product.

### Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

### Appropriate technical measures

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

Do not recirculate outlet air that contain the substances.

#### Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

#### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

### 8.3. Individual protection measures, such as personal protective equipment

#### Generally

Use only UKCA marked protective equipment.

#### Respiratory Equipment

Work situation	Type	Class	Colour	Standards
In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Preferably a compressed airline breathing apparatus. Breathing apparatus with filter.	Combination Filter A2B2E2K2	Class 2 (medium capacity)	Brown/Gray/Yellow /Green	EN14387



#### Skin protection

Recommended	Type/Category	Standards
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-



#### Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion	Neoprene (Neoprene)	-	> 240	EN374-2, EN374-3, EN388, EN407, EN511



#### Eye protection

Work situation	Type	Standards
When there is risk of splash- / intermittent exposure	Face shield	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

Colour

Various colours

Odour / Odour threshold

Testing not relevant or not possible due to the nature of the product.

pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm<sup>3</sup>)

1.22

Kinematic viscosity

No information available as testing has not been completed.

Particle characteristics

Not applicable - product is a liquid

Phase changes

Melting point/Freezing point (°C)

No information available as testing has not been completed.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

100

Vapour pressure

No information available as testing has not been completed.

Relative vapour density

No information available as testing has not been completed.

Decomposition temperature (°C)

No information available as testing has not been completed.

Data on fire and explosion hazards

Flash point (°C)

75

Ignition (°C)

Testing not relevant or not possible due to the nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Evaporation rate (n-butylacetate = 100)

No information available as testing has not been completed.

VOC (g/l)

30

Other physical and chemical parameters

No data available.

## SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions



Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

None known.

#### 10.4. Conditions to avoid

None known.

#### 10.5. Incompatible materials

Strong oxidizing agents

#### 10.6. Hazardous decomposition products

Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

##### Acute toxicity

Product/substance	2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	5660 mg/kg
Other information	

Product/substance	2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether
Test method	
Species	Rabbit
Route of exposure	Dermal
Test	LD50
Result	2764 mg/kg
Other information	

Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rat
Route of exposure	Oral
Test	LD50
Result	550 mg/L
Other information	

Product/substance	reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)
Test method	
Species	Rat
Route of exposure	Dermal
Test	LD50
Result	200-1000 mg/L
Other information	

##### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

##### Serious eye damage/irritation

Based on available data, the classification criteria are not met.

##### Respiratory sensitisation

Based on available data, the classification criteria are not met.

##### Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

##### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

##### Carcinogenicity

Suspected of causing cancer.

##### Reproductive toxicity

Based on available data, the classification criteria are not met.

##### STOT-single exposure

Based on available data, the classification criteria are not met.

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

##### Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion.

##### Endocrine disrupting properties

None known.

##### Other information

Melamine has been classified by IARC as a group 2B carcinogen.

2-butoxyethanol;2-butoxyethanol; ethylene glycol monobutyl ether;ethylene glycol monobutyl ether;butyl cellosolve has been classified by IARC as a group 3 carcinogen.

## SECTION 12: Ecological information

#### 12.1. Toxicity

Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

Product/substance 2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether

Test method

Potential bioaccumulation No data available.

LogPow 0,68

BCF 2,9

Other information

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

#### 12.6. Endocrine disrupting properties

None known.

#### 12.7. Other adverse effects

None known.

## SECTION 13: Disposal considerations

#### Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 7 - Carcinogenic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### EWC code

Not applicable.

#### Specific labelling

Not applicable.

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

\* Packing group

\*\* Environmental hazards

#### Additional information

Not dangerous goods according to ADR, IATA and IMDG.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

Not applicable.

#### UK-REACH, Annex XVII

2-(2-butoxyethoxy)ethanol;diethylene glycol monobutyl ether is subject to restrictions, UK-REACH annex XVII (entry 55).

#### Additional information

Not applicable.

#### Sources

The Management of Health and Safety at Work Regulations 1999.

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

### 15.2. Chemical safety assessment

No

## SECTION 16: Other information

### Full text of H-phrases as mentioned in section 3

H301, Corrosive to the respiratory tract.

H302, Toxic if swallowed.

H302, Harmful if swallowed.

H310, Fatal in contact with skin.

H312, Harmful in contact with skin.

H314, Causes severe skin burns and eye damage.

H315, Causes skin irritation.

H317, May cause an allergic skin reaction.

H318, Causes serious eye damage.

H319, Causes serious eye irritation.

Compiled in accordance with REACH Regulation (EC) No 1907/2006, as retained and amended in UK law

H330, Fatal if inhaled.  
H332, Harmful if inhaled.  
H351, Suspected of causing cancer.  
H373, May cause damage to organs through prolonged or repeated exposure.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

#### The safety data sheet is validated by

EcoOnline

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en