


Aruba hH


Aruba hH is a tough and reliable humidity resistant ceiling tile. Stable at up to 99% Relative Humidity (RH), it is ideal for high humidity areas such as changing rooms.

Key Features

- Up to 99% RH
- Available in Board edge
- Offers Class C sound absorption and good attenuation for excellent acoustic performance
- Available in Global White, giving warm and damp spaces a brighter and cooler appearance
- Ideal for high humidity areas such as changing rooms
- Excellent technical performance in humid conditions when used alongside Prelude 24 Corrosive Resistant suspended ceiling grid



Edge Detail Board



Thickness (mm) 15

Modules (mm) 600 x 600 5499M

Suspension Systems Prelude 24 XL² / TLS
Prelude 24 Corrosive Resistant
Prelude 24 Sixty² XL² / TLS

Colour Global White

Sustainability



44






A




EN 13964 / E1



Acoustics



EN ISO 354 & EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1


	Hz α_p									
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	0.60	34 dB	C	0.55	0.35	0.45	0.60	0.60	0.60	0.60

Fire Reaction




Euroclass A2-s1, d0
EN 13501-1


Performances & Features





85%




99% RH








Lifetime Guarantee





30 Year System Guarantee



3.6 Kg/m²







BIM READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 138.2.06.23