



Aruba Max

Aruba Max with its microperforated, finely sanded surface, offers improved levels of sound absorption and sound attenuation, making it a great choice for classrooms and other areas requiring Class C sound absorption.

Key Features

- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Balanced acoustical absorption performance of 0.65 α_w and sound attenuation of 35dB
- Fully painted, reinforced edges for a more robust tile and greater durability
- Easy to handle and re-engineered for a better, easier fit
- Ideal for classroom and general teaching conditions



Edge Detail	Board		Tegular24		Tegular15																									
Thickness (mm)	18		18		18																									
Modules (mm)	600 x 600 5471M 1200 x 600 5472M		600 x 600 5473M		600 x 600 5475M																									
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS		Prelude 15 TL/ XL ² Interlude HRC XL ² Silhouette XL ²																									
Colour	Global White																													
Sustainability	<div><div> 46</div><div></div><div> A</div><div> EN 13964 / E1</div><div></div></div>																													
Acoustics	<div><div> EN ISO 354 & EN ISO 11654</div><div> EN ISO 10848-2 & EN ISO 717-1</div><div> EN ISO 140-3 & EN ISO 717-1</div><div><table><thead><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>R_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>Board, Tegular24, Tegular15</td><td>0.65</td><td>35 dB</td><td>17 dB</td><td>C</td><td>0.60</td><td>0.35</td><td>0.45</td><td>0.60</td><td>0.65</td><td>0.70</td><td>0.65</td></tr></tbody></table></div></div>							α_w	D _{nfw}	R _w	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65
	α_w	D _{nfw}	R _w	Class	NRC	125	250	500	1000	2000	4000																			
Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65																			
Fire Reaction	<div><div></div><div>A2-s1, d0 EN 13501-1</div></div>																													
Performances & Features	<div><div> 85%</div><div> 95% RH</div><div></div><div></div><div><div>Lifetime Guarantee</div></div><div><div>30 Year System Guarantee</div></div><div> 4.3 Kg/m²</div><div></div><div></div><div><div>BIM READY</div></div></div>																													
Custom Options	<div><div></div><div>Dimensions</div></div>																													

Colours

Add the following codes to the end of the product code for more colour options

 RAL 9003	 RAL 260 90 05	 RAL 130 90 10	 RAL 080 90 10	 RAL 050 90 10	 RAL 010 90 10	 RAL 340 90 05	 RAL 050 70 10
 RAL 000 85 00	 RAL 260 80 15	 RAL 130 80 30	 RAL 075 80 40	 RAL 050 80 30	 RAL 020 80 20	 RAL 340 80 20	 RAL 050 70 20
 RAL 000 65 00	 RAL 260 50 25	 RAL 140 50 30			 RAL 020 60 40	 RAL 340 60 35	 RAL 040 30 30
 RAL 000 30 00	 RAL 260 30 20	 RAL 140 30 20			 RAL 020 30 40	 RAL 340 30 30	 RAL 8004
 RAL 9005	 RAL 5015	 RAL 6037	 RAL 1003	 RAL 2009	 RAL 3020	 RAL 4006	

We recommend ordering a full colour sample prior to specification and ordering. If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com.

Please note that even though great care has been taken to ensure correct colour match, colours can only be as accurate as the printing process allows.

Every monitor or mobile display has a different capability to display colours, and every individual may see these colours differently.



Order a sample

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 134.2.05.23