




Oplia hA+

Oplia hA+ is a smooth laminated finish and offers the highest level of sound absorption ($1.00 \alpha_w$), making it ideal for open plan spaces.

Key Features

- Excellent sound absorption: 1.00 α_w
- High light reflectance: 85%
- Better finish and more durable edges
- Ideal for open spaces, call centres, open plan offices and SEN schools



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	20	20	20
Modules (mm)	600 x 600 3861M 1200 x 600 3863M	600 x 600 3866M	600 x 600 2097M
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 15 TL/ XL ² Interlude HRC XL ² Silhouette XL ²

Sustainability



73



A+



EN 13964 / E1



Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Results based on Global White tiles

	Hz α_p										
	α_w	Dnfw	Rw	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	1.00	33 dB	15 dB	A	0.95	0.65	0.80	0.95	0.95	1.00	1.00

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



95% RH



30 Year
System
Guarantee



3.1 Kg/m²



ISO 5



ISO 14644-1



BIM
READY

Custom Options



Dimensions

Colour

Global White and colour options

Colours

Add the following codes to the end of the product code for more colour options

 GY1 RAL 000 85 00	 BL5 RAL 260 90 05	 GR5 RAL 130 90 10	 YE3 RAL 080 90 10	 OR3 RAL 050 90 10	 RE5 RAL 010 90 10	 PU5 RAL 340 90 05	 BR4 RAL 050 70 10
 GY2 RAL 000 65 00	 BL4 RAL 260 80 15	 GR4 RAL 130 80 30	 YE2 RAL 075 80 40	 OR2 RAL 050 80 30	 RE4 RAL 020 80 20	 PU4 RAL 340 80 20	 BR3 RAL 050 70 20
 GY3 RAL 000 30 00	 BL3 RAL 260 50 25	 GR3 RAL 140 50 30	 YE1 RAL 1003	 OR1 RAL 2009	 RE3 RAL 020 60 40	 PU3 RAL 340 60 35	 BR2 RAL 040 30 30
 BK1 RAL 9005	 BL2 RAL 260 30 20	 GR2 RAL 140 30 20			 RE2 RAL 020 30 40	 PU2 RAL 340 30 30	 BR1 RAL 8004
	 BL1 RAL 5015	 GR1 RAL 6037			 RE1 RAL 3020	 PU1 RAL 4006	



Order a sample

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 170.2.11.23