






Oplia dB

Oplia dB is a smooth laminated finish providing enhanced sound attenuation performance for improving the privacy between adjacent spaces.

Key Features

- Excellent level of sound attenuation: up to 41 dB
- High light reflectance: 86%
- Better finish and more durable edges
- ISO 5 / A+
- Ideal for individual offices

Edge Detail	Board	Tegular24	Tegular15
			
Thickness (mm)	19	19	19
Modules (mm)	600 x 600 3191M	600 x 600 3192M	600 x 600 2095M
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette XL ²

Sustainability



39



A+



EN 13964 / E1



Colour

Global white

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Hz α_p

	α_w	D _{nfw}	R _w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.60(H)	41 dB	21 dB	C	0.65	0.30	0.40	0.55	0.70	0.85	0.95

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



86%



95% RH



30 Year
System
Guarantee



7.6 Kg/m²



ISO 5



ISO 14644-1



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 171.1.11.23