




Oplia hA dB

Oplia hA dB combines the smooth Oplia laminated appearance with the highest levels of sound absorption and sound attenuation in one tile, providing a solution for flexible working spaces.

Key Features

- /// Oplia hA dB includes a large selection of sizes and quality edge details enhancing durability
- /// The best acoustical combination of high sound absorption and high sound attenuation properties
- /// Ideal for open plan offices, board rooms, SEN schools and libraries



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	40	40	40
Modules (mm)	600 x 600 5044M 1200 x 600 5045M	600 x 600 5104M	600 x 600 5114M
Suspension Systems	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 24 XL ² / TLS Prelude 24 Sixty ² XL ² / TLS	Prelude 15 TL / XL ² Interlude HRC XL ² Silhouette XL ²

Sustainability



44



A+



EN 13964 / E1

Colour

Global white

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Hz α_p

	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.90	40 dB	20 dB	A	0.85	0.35	0.60	0.90	1.00	1.00	1.00

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



95% RH



ISO 5

ISO 14644-1



30 Year
System
Guarantee



6.2 Kg/m²



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 172.1.11.23