



Aquabloc

Aquabloc is a hydrated calcium silicate ceiling tile offering 100% RH performance and is suitable for use in areas subject to extremes of humidity and temperature.


Key Features

- ✓ 100% RH resistance
- ✓ Suitable for extreme temperatures and high humidity conditions
- ✓ Resistant to damage
- ✓ Ideal for spas and water parks



Edge Detail

Board



Thickness (mm)

6

Modules (mm)

600 x 600 2100M

Suspension Systems

Gridline 24 Butt Cut / Joggled
Gridline 24 Corrosive Resistant
Gridline 24 Clean

Colour

Global White

Sustainability



30



EN 13964 / E1

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 21040-9
& EN ISO 717-1

| | α_w | D_{nfw} | Class | NRC | Hz α_p | | | | | |
|-------|------------|-----------|-------|------|---------------|------|------|------|------|------|
| | | | | | 125 | 250 | 500 | 1000 | 2000 | 4000 |
| Board | 0.10(L) | 37 dB | - | 0.10 | 0.25 | 0.15 | 0.10 | 0.10 | 0.10 | 0.05 |

Fire Reaction



Euroclass A1
EN 13501-1

Performances & Features



84%



100% RH



8.0 Kg/m²



30 Year
System
Guarantee

BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 100.3.03.25