


















## Titan (100% RH)

With its unique high density mineral composition, Titan is steam resistant and will retain its physical integrity even when subjected to 100% RH. It also features a washable finish and is lightly fissured to provide acoustic performance.

## Key Features

- 100% RH resistance
- Durable, washable and scrubbable
- Resistant to growth of mould, mildew and bacteria
- Good balance between sound attenuation and absorption
- Ideal for swimming pools, locker rooms, shower areas and indoor parking areas



Edge Detail	Board									
										
Thickness (mm)	15									
Modules (mm)	600 x 600 ..... 607M									
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant <sup>1</sup> Gridline 24 Clean					*Titan must be installed on Gridline 24 Corrosive Resistant grid where humidity regularly exceeds 95% RH. Titan may need to have Main Runners at 600 mm centres due to increased weight in high humidity conditions.				
Colour	Global White									
Sustainability	 37		 A+	 EN 13964 / E1						
Acoustics	 EN ISO 354 & EN ISO 11654		 EN ISO 10848-2 & EN ISO 717-1							
		$\alpha_w$	$D_{nfw}$	Class	NRC	125	250	Hz $\alpha_p$		
Board		0.55(H)	–	D	0.55	0.40	0.35	0.45	0.65	0.90 0.95
Fire Reaction	 Euroclass A1 EN 13501-1									
Performances & Features	 79%	 7.3Kg/m <sup>2</sup> 20 Kg/m <sup>2</sup> > if wet								
	 100% RH									

While this product is suitable for high humidity environments, it is not suitable to be fitted directly over a swimming pool.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 234.2.11.25