







Aruba dB

The higher attenuation performance of Aruba dB offers a perfect solution for improving the privacy between adjacent spaces. Whilst the class-leading whiteness helps to create spaces that are brighter and better, and which offer a greater sense of well-being for your customers.

Key Features

- Excellent sound attenuation (39 dB sound reduction) to eliminate the need for sound barriers in close office applications
- Enhanced acoustical absorption performance of 0.60 α_w for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Easy to handle and re-engineered for a better, easier fit
- Ideal for individual offices and board rooms



Edge Detail	Board	Tegular24	Tegular15
			
Thickness (mm)	19	19	19
Modules (mm)	600 x 600 5477M	600 x 600 5479M	600 x 600 5481M
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut Gridline 15 Shadow

Colour Global White

Sustainability



37



A+



EN 13964 / E1



Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.60	39 dB	20 dB	C	0.55	0.35	0.40	0.60	0.65	0.75	0.65

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



95% RH



7.9 Kg/m²



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 135.4.05.25