

Key Features

- // Improved aesthetics with discreet perforations, a smoother finish and a class-leading whiteness
- // Enhanced acoustical absorption performance of $0.60 \, Q_{\rm w}$ for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- Mix and match modules for increased flexibility and a more complete project solution
- Easy to handle and re-engineered for a better, easier fit
- Ideal for every space



Edge Detail	Board	Tegular24					Tegular15				
	<u>Q</u>	6.5 7 24									
Thickness (mm)	15		15								
Modules (mm)	600 x 600	600 x 600				600 x 600					
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 E	Gridline 15 Butt Cut / Joggled Gridline 15 Shadow								
Colour	Global White										
Sustainability							OOR AL	R CONTORI			
	44	A EN 13964 / E1					IFIED	PROD			
Acoustics	<u>***</u>						Results	based o	n Global V	White tiles	
	ENISO &ENISO						Hz	. α _P			
	α_{v}	D _{nfw}	Class	NRC	125	250	500	1000	2000	4000	

Fire Reaction



Euroclass A2-s1, d0 EN 13501-1

Performances & Features



85%

Board, Tegular24, Tegular15



95% RH

0.60



34 dB

C

0.55

0.35

0.45





0.60

0.60



0.60



3.6 Kg/m²







If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

TDS 133.8.05.25

