







Fission FT

The non-directional fine fissured surface provides a solution for providing Class C sound absorption.

Key Features

- Good sound absorption: 0.60(H) α_w
- Ideal for storage facilities, corridor and warehouses



Edge Detail	Board	Tegular24	Tegular15																																							
																																										
Thickness (mm)	15	15	15																																							
Modules (mm)	600 x 6009121M 1200 x 6009120M	600 x 6009122M	600 x 6009202M																																							
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled																																							
Colour	Global White / Black (available for 9121M only)																																									
Sustainability	 51%		 A+	 EN 13964 / E1																																						
Acoustics	 EN ISO 354 & EN ISO 11654	 EN ISO 21040-9 & EN ISO 717-1	Hz α_p <table><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board, Tegular24, Tegular15</td><td>0.60(H)</td><td>34 dB</td><td>C</td><td>0.65</td><td>0.40</td><td>0.40</td><td>0.55</td><td>0.80</td><td>0.85</td><td>0.85</td></tr><tr><td>Board (Black)</td><td>0.60(H)</td><td>34 dB</td><td>C</td><td>0.65</td><td>0.35</td><td>0.40</td><td>0.55</td><td>0.75</td><td>0.80</td><td>0.85</td></tr></table>								α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular24, Tegular15	0.60(H)	34 dB	C	0.65	0.40	0.40	0.55	0.80	0.85	0.85	Board (Black)	0.60(H)	34 dB	C	0.65	0.35	0.40	0.55	0.75	0.80	0.85
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000																																
Board, Tegular24, Tegular15	0.60(H)	34 dB	C	0.65	0.40	0.40	0.55	0.80	0.85	0.85																																
Board (Black)	0.60(H)	34 dB	C	0.65	0.35	0.40	0.55	0.75	0.80	0.85																																
Fire Reaction	 Euroclass A2-s1, d0 EN 13501-1																																									
Performances & Features	 85% White	 95% RH	 3.4 Kg/m ²		 30 Year System Guarantee	 BIM READY																																				

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 076.6.05.25