



## Oplia Triangle












Oplia Triangle is an exciting addition to the Oplia product family. These suspended ceiling tiles are cut into triangles and are available in 35 exciting colours, allowing you to create acoustic ceilings that make a real design statement.

## Key Features

Oplia Triangle is a unique decorative ceiling tile that doesn't compromise on technical performance.

- With Class C sound absorption and excellent sound attenuation, it's a striking addition to any interior
- The triangular shape makes this ceiling tile particularly useful for wayfinding and zoning when used in combination with coloured tiles
- Compatible with Zentia's Gridline 24 suspended ceiling grid using a standard main runner, a unique cross tee and an innovative angled nodal bracket
- 30 Year System Guarantee



Edge Detail	Board																																					
																																						
Thickness (mm)	17																																					
Modules (mm)	1200 x 1200 x 1200 ..... BPTT2802M																																					
Suspension Systems	Gridline 24 Butt Cut / Joggled																																					
Sustainability	<div><div>80</div></div> <div><div>EN 13964 / E1</div></div>																																					
Acoustics	<div><div><div>EN ISO 354 &amp; EN ISO 11654</div></div><div><div>EN ISO 10848-2 &amp; EN ISO 717-1</div></div><div><div>EN ISO 140-3 &amp; EN ISO 717-1</div></div></div> <table><thead><tr><th></th><th><math>\alpha_w</math></th><th><math>D_{nfw}</math></th><th><math>R_w</math></th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th colspan="4">Hz <math>\alpha_p</math></th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>Triangle</td><td>0.60 (MH)</td><td>–</td><td>–</td><td>C</td><td>0.70</td><td>0.35</td><td>0.35</td><td>0.55</td><td>0.85</td><td>1.00</td><td>1.00</td></tr></tbody></table>													$\alpha_w$	$D_{nfw}$	$R_w$	Class	NRC	125	250	Hz $\alpha_p$				2000	4000	Triangle	0.60 (MH)	–	–	C	0.70	0.35	0.35	0.55	0.85	1.00	1.00
	$\alpha_w$	$D_{nfw}$	$R_w$	Class	NRC	125	250	Hz $\alpha_p$				2000	4000																									
Triangle	0.60 (MH)	–	–	C	0.70	0.35	0.35	0.55	0.85	1.00	1.00																											
Fire Reaction	<div><div>Euroclass A2-s1, d0 EN 13501-1</div></div>																																					
Performances & Features	<div><div><div>95% RH</div></div><div><div>30 Year System Guarantee</div></div></div> <div><div><div>4.6 Kg/m<sup>2</sup></div></div><div><div>BIM READY</div></div></div>																																					

