






















Aruba hH (High Humidity)

Aruba hH (High Humidity) is a tough and reliable humidity resistant ceiling tile. Stable at up to 99% Relative Humidity (RH), it is ideal for high humidity areas such as changing rooms.

Key Features

- Up to 99% RH
- Available in Board edge
- Offers Class C sound absorption and good attenuation for excellent acoustic performance
- Available in Global White, giving warm and damp spaces a brighter and cooler appearance
- Ideal for high humidity areas such as changing rooms
- Excellent technical performance in humid conditions when used alongside Gridline 24 Corrosive Resistant suspended ceiling grid



Edge Detail	Board										
											
Thickness (mm)	15										
Modules (mm)	600 x 600 5499M										
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant										
Colour	Global White										
Sustainability	 44		 A	 EN 13964 / E1							
Acoustics	 EN ISO 354 & EN ISO 11654		 EN ISO 10848-2 & EN ISO 717-1								
	α_w		D_{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	0.60		34 dB	C	0.55	0.35	0.45	0.60	0.60	0.60	0.60
Fire Reaction	 Euroclass A2-s1, d0 EN 13501-1										
Performances & Features	 85%	 99% RH			 Lifetime Guarantee			 30 Year System Guarantee			
	 3.6 Kg/m ²			 BIM READY							

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 138.5.03.25