



















## Oplia dB

Oplia dB is a smooth laminated finish providing enhanced sound attenuation performance for improving the privacy between adjacent spaces.

## Key Features

- Excellent level of sound attenuation: up to 41 dB
- High light reflectance: 86%
- Better finish and more durable edges
- ISO 5 / A+
- Ideal for individual offices

Edge Detail	Board		Tegular24				Tegular15																																																									
																																																																
Thickness (mm)	19		19				19																																																									
Modules (mm)	600 x 600 .....3191M		600 x 600 .....3192M				600 x 600 .....2095M																																																									
Suspension Systems	Gridline 24 Butt Cut / Joggled		Gridline 24 Butt Cut / Joggled				Gridline 15 Butt Cut / Joggled Gridline 15 Shadow																																																									
Sustainability	 39		 A+		 EN 13964 / E1																																																											
Colour	Global white																																																															
Acoustics	<div><div> EN ISO 354 &amp; EN ISO 11654</div><div> EN ISO 10848-2 &amp; EN ISO 717-1</div><div> EN ISO 140-3 &amp; EN ISO 717-1</div></div> <table><thead><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr></thead><tbody><tr><td></td><td><math>\alpha_w</math></td><td>D<sub>nfw</sub></td><td>R<sub>w</sub></td><td>Class</td><td>NRC</td><td>125</td><td>250</td><td>500</td><td>1000</td><td>2000</td><td>4000</td><td></td></tr><tr><td>Board, Tegular24, Tegular15</td><td>0.60(H)</td><td>41 dB</td><td>21 dB</td><td>C</td><td>0.65</td><td>0.30</td><td>0.40</td><td>0.55</td><td>0.70</td><td>0.85</td><td>0.95</td><td></td></tr></tbody></table>																																							$\alpha_w$	D <sub>nfw</sub>	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000		Board, Tegular24, Tegular15	0.60(H)	41 dB	21 dB	C	0.65	0.30	0.40	0.55	0.70	0.85	0.95	
	$\alpha_w$	D <sub>nfw</sub>	R <sub>w</sub>	Class	NRC	125	250	500	1000	2000	4000																																																					
Board, Tegular24, Tegular15	0.60(H)	41 dB	21 dB	C	0.65	0.30	0.40	0.55	0.70	0.85	0.95																																																					
Fire Reaction	<div><div>Euroclass A2-s1, d0 EN 13501-1</div></div>																																																															
Performances & Features	<div><div>86%</div></div>	<div><div>95% RH</div></div>	<div></div>	<div><div>7.6 Kg/m<sup>2</sup></div></div>	<div><div>ISO 5 ISO 14644-1</div></div>	<div><div>30 Year System Guarantee</div></div>	<div><div>BIM READY</div></div>																																																									

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 171.6.05.25