

Key Features

- // Improved aesthetics with discreet perforations, a smoother finish and a class-leading whiteness
- Enhanced acoustical absorption performance of 0.60 α_{w} for better acoustic comfort
- Fully painted, reinforced edges for a more robust tile and greater durability
- Mix and match modules for increased flexibility and a more complete project solution
- Easy to handle and re-engineered for a better,
- Ideal for every space



Edge Detail	Board	Tegular24	Tegular15
	124	6.5 1 24	15
Thickness (mm)	15	15	15
Modules (mm)	600 x 600	600 x 600	600 x 600
Suspension Systems	Gridline 24 Butt Cut / Joggled Available in Nexus Layouts	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Gridline 15 Shadow
Colour	Global White		
Sustainability	44	A EN 13964/E1	RAIR COMPE
Acoustics		A EN 13904 / E1	Results based on Global White tiles
ACOUSTICS	<u>*************************************</u>	7 2	Results based on Global White tiles







 $Hz\,\alpha_{\text{\tiny P}}$ α_{w} $D_{n f w} \\$ Class NRC 125 250 500 1000 2000 4000 Board, Tegular24, Tegular15 0.60 34 dB C 0.55 0.35 0.45 0.60 0.60 0.60 0.60

Fire Reaction



Euroclass A2-s1, d0 EN 13501-1

Performances & Features



85%



95% RH











 $3.6 \, \text{Kg/m}^2$







If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

TDS 133.9.09.25

