



Prestige

Prestige not only offers a finely textured and durable surface with a brighter 'blue-white' colour and high light reflectance, it also offers a balance of both sound absorption and sound attenuation. Providing the perfect balance between open spaces or personal office.

Key Features

- // Good sound absorption: up to 0.70 α_w
- // Very high light reflectance: 87%
- // Reinforced scratch resistant face
- // Better finish and more durable edges
- // ISO 5 / A+
- // 30 year system guarantee
- // Ideal for meeting rooms or waiting areas
- // SL2 Planks: Ideal for both open areas and corridors



Edge Detail	Board	Tegular24	Tegular15	Integra	Conceal	SL2
Thickness (mm)	19	19	19	20	19	19
Modules (mm)	600 x 600 ..7661M 1200 x 600 ..7663M	600 x 600 ..7664M 1200 x 600 ..7666M	600 x 600 ..7674M 1200 x 600 ..7677M	600 x 600 ..7681M	600 x 600 ..7715M 1200 x 600 ..7716M	1500 x 300 ..7699M* 1800 x 300 ...7701*
Suspension Systems	Prelude 24 XL ² /TLS Prelude 24 Sixty ² XL ² /TLS	Prelude 24 XL ² /TLS Prelude 24 Sixty ² XL ² /TLS	Prelude 15 TL/XL ² Interlude HRC XL ² Silhouette XL ²	Prelude 24 XL ² /TLS Prelude 24 Sixty ² XL ² /TLS	System Z – L-Bar	System Z - T-Bar System Z - Z-Bar

Colours

Add the following codes to the end of the product code for more colour options

RAL 9003	RAL 260 90 05	RAL 130 90 10	RAL 080 90 10	RAL 050 90 10	RAL 010 90 10	RAL 340 90 05	RAL 050 70 10
RAL 000 85 00	RAL 260 80 15	RAL 130 80 30	RAL 075 80 40	RAL 050 80 30	RAL 020 80 20	RAL 340 80 20	RAL 050 70 20
RAL 000 65 00	RAL 260 50 25	RAL 140 50 30			RAL 020 60 40	RAL 340 60 35	RAL 040 30 30
RAL 000 30 00	RAL 260 30 20	RAL 140 30 20			RAL 020 30 40	RAL 340 30 30	RAL 8004
RAL 9005	RAL 5015	RAL 6037	RAL 1003	RAL 2009	RAL 3020	RAL 4006	

*excluding SL2

Sustainability



41



A+¹



EN 13964 / E1

¹Except Vector: A

Acoustics



EN ISO 354 & EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1



EN ISO 140-3 & EN ISO 717-1

	α_w	D _{nfw}	R _w	Class	NRC	Hz α_p						
						125	250	500	1000	2000	4000	
Board, Tegular24, Tegular15	0.70(H)	-	-	C	0.70	0.45	0.50	0.60	0.80	0.85	0.95	
Integra	0.70(H)	-	-	C	0.65	0.40	0.50	0.60	0.70	0.75	0.90	
Conceal	0.70(H)	-	-	C	0.75	0.40	0.50	0.65	0.85	0.95	1.00	
SL2	0.65(H)	40 dB	-	C	0.65	0.35	0.45	0.55	0.75	0.90	1.00	

Fire Reaction



A2-s1, d0
EN 13501-1

Performances & Features



87%



ISO 5



ISO 14644-1



30 Year System Guarantee



95% RH



5.0 Kg/m² Board, Tegular24, Tegular15, Conceal, SL2
5.8 Kg/m² Integra



BIM READY

Custom Options



Dimensions



Order a sample

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

156.1.10.23