



Aquabloc

Aquabloc is a hydrated calcium silicate ceiling tile offering 100% RH performance and is suitable for use in areas subject to extremes of humidity and temperature.




Key Features

- 100% RH resistance
- Suitable for extreme temperatures and high humidity conditions
- Resistant to damage
- Ideal for spas and water parks





Edge Detail Board



Thickness (mm)	6
Modules (mm)	600 x 600 2100M
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant Prelude 24 Clean Room
Colour	Global White

Sustainability	 30	 EN 13964 / E1
-----------------------	--	---

Acoustics	 EN ISO 354 & EN ISO 11654	 EN ISO 21040-9 & EN ISO 717-1								
	α_w	D_{nfw}	Class	NRC	125	250	500	1000	2000	4000
Board	0.10(L)	37 dB	-	0.10	0.25	0.15	0.10	0.10	0.10	0.05

Fire Reaction	 Euroclass A1 EN 13501-1
----------------------	--

Performances & Features	 84%	 100% RH			
	 8.0 Kg/m ²				

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 100.2.03.24