



Neeva


The smooth laminated finish of the Neeva products combines Class A sound absorption and aesthetics.

Key Features

- Excellent sound absorption: up to 1.00 α_w
- High light reflectance: 82%
- Fibre glass fleece on the back to add strength
- Ideal for open spaces, call centres and libraries



Edge Detail Board



Thickness (mm) 15 / 18

Modules (mm) 600 x 600 x 15..... 2691M
1200 x 1200 x 18 2406M

Suspension Systems Gridline 24 Butt Cut / Joggled
Gridline 24 Corrosive Resistant
Prelude 24 Sixty²

Colour Global White

Sustainability




20






EN 13964 / E1


Acoustics



EN ISO 354 & EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1



EN ISO 140-3 & EN ISO 717-1

	α_w	D _{nfw}	R _w	Class	NRC	Hz α_p						
						125	250	500	1000	2000	4000	
Board (15mm)	1.00	-	7 dB	A	0.95	0.40	0.90	1.00	0.90	1.00	1.00	
Board (18mm)	1.00	24 dB	-	A	0.95	0.40	0.85	1.00	0.90	1.00	0.95	

Fire Reaction



A1
EN 13501-1

Performances & Features



82%



95% RH







1.2 Kg/m²
Board (15mm)



1.3 Kg/m²
Board (18mm)





If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email info@zentia.com

TDS 073.3.03.24