

# **Key Features**

- Improved aesthetics with discreet perforations
- // Enhanced acoustical absorption performance of  $0.60~\mbox{Q}_{\rm w}$  for better acoustic comfort
- Mix and match modules for increased flexibility and a more complete project solution
- Easy to handle and re-engineered for a better fit
- Ideal for every space
- Combination of coloured tiles can be useful for wayfinding and zoning



Edge Detail	Board	Tegular24	Tegular15			
	124	6.5 1 24				
Thickness (mm)	15	15	15			
Modules (mm)	600 x 600	600 x 600 6572M 1200 x 600 6573M	600 x 600 6574N 1200 x 600 6575N			
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Interlude HRC Silhouette			
Sustainability						





44

EN 13964 / E1

### **Acoustics**



& EN ISO 11654



EN ISO 10848-2 & EN ISO 717-1 Results based on painted colour tiles

	Q E11150 11054	Hz $\alpha_P$								
	$\alpha_{\sf w}$	D <sub>nfw</sub>	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15	0.60	-	С	0.55	0.50	0.45	0.60	0.60	0.55	0.55

# **Fire Reaction**



Euroclass A2-s1, d0 EN 13501-1

# Performances & Features



95% RH







3.6 Kg/m<sup>2</sup>





#### Colours

### Add the following codes to the end of the product code when ordering



We recommend ordering a full colour sample prior to specification and ordering. If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com.

Please note that even though great care has been taken to ensure correct colour match, colours can only be as accurate as the printing process allows.

Every monitor or mobile display has a different capability to display colours, and every individual may see these colours differently.



Order a sample





