



Acousta

Acousta has a fine textured surface and offers Class A sound absorption.

Key Features

- Excellent sound absorption: up to 1.00 α_w
- High light reflectance: 86%
- Excellent mechanical strength
(fibreglass fleece at the back)
- Ideal for open spaces, call centres and libraries



Edge Detail	Board	Tegular24	Tegular15	Integra
Thickness (mm)	20	20	20	22
Modules (mm)	600 x 600 x 20 ...2285M	600 x 600 x 20 ...2286M	600 x 600 x 20 ...2287M	600 x 6002288M 1200 x 6002289M
Suspension Systems	Gridline 24 Butt Cut/ Joggled	Gridline 24 Butt Cut/ Joggled	Gridline 15 Butt Cut / Joggled Gridline 15 Shadow	Gridline 24 Butt Cut/ Joggled
Colour	Global White			

Sustainability



80



EN 13964 / E1

Acoustics



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

	&ENISO 11654	&ENISO 117-1	&ENISO 117-1	Hz α_p							
	α_w	D _{nFw}	R _w	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15, Integra	1.00	28 dB	13 dB	A	0.95	0.60	0.90	0.95	0.95	1.00	1.00

Fire Reaction



Euroclass A2-s2,d0
EN 13501-1

Performances & Features



86%



95% RH



2.0 Kg/m² (20mm)
2.8 Kg/m² (22mm)



30 Year
System
Guarantee



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 205.2.11.25