




Oplia hA+

Oplia hA+ is a smooth laminated finish and offers the highest level of sound absorption ($1.00 \alpha_w$), making it ideal for open plan spaces.

Key Features

- Excellent sound absorption: $1.00 \alpha_w$
- High light reflectance: 85%
- Better finish and more durable edges
- Ideal for open spaces, call centres, open plan offices and SEN schools



| Edge Detail | Board | Tegular24 | Tegular15 |
|--------------------|---|--------------------------------|--|
| | | | |
| Thickness (mm) | 20 | 20 | 20 |
| Modules (mm) | 600 x 600 3861M 1200 x 600 3863M | 600 x 600 3866M | 600 x 600 2097M |
| Suspension Systems | Gridline 24 Butt Cut / Joggled | Gridline 24 Butt Cut / Joggled | Gridline 15 Butt Cut / Joggled Gridline 15 Shadow |

Colour Global White

Sustainability



44



A+



EN 13964 / E1



Acoustics

Results based on Global White tiles



EN ISO 354
& EN ISO 11654



EN ISO 10848-2
& EN ISO 717-1



EN ISO 140-3
& EN ISO 717-1

Hz α_p

| | α_w | D_{nfw} | R_w | Class | NRC | 125 | 250 | 500 | 1000 | 2000 | 4000 |
|-----------------------------|------------|-----------|-------|-------|------|------|------|------|------|------|------|
| Board, Tegular24, Tegular15 | 1.00 | 33 dB | 15 dB | A | 0.95 | 0.65 | 0.80 | 0.95 | 0.95 | 1.00 | 1.00 |

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



85%



95% RH



ISO 5



ISO 14644-1



3.1 Kg/m²



30 Year
System
Guarantee



BIM
READY

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 170.5.03.25