







## Oplia hA

Oplia hA is a smooth laminated finish and Class A sound absorption, making it ideal for open plan areas.

## Key Features

- Excellent sound absorption: up to 0.95  $\alpha_w$
- Better finish and more durable edges
- Ideal for open spaces, call centres, libraries and schools



Edge Detail	Board	Tegular24	Tegular15
			
Thickness (mm)	15	15	15
Modules (mm)	600 x 600 x 15..... 3819M 1200 x 600 x 15..... 3821M	600 x 600 x 15..... 5173M 1200 x 600 x 15..... 5177M	600 x 600 x 15..... 5174M 1200 x 600 x 15..... 5178M
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut / Joggled Gridline 15 Shadow

Colour Global White

## Sustainability



44



A+



EN 13964 / E1

## Acoustics

Results based on Global White tiles



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1



EN ISO 140-3  
& EN ISO 717-1

	&EN ISO 11634	&EN ISO 1171	&EN ISO 1171								
	$\alpha_w$	$D_{nfw}$	$R_w$	Class	NRC	125	250	500	1000	2000	4000
Board, Tegular24, Tegular15 (15mm)	0.95	–	–	A	0.90	0.60	0.80	0.95	0.90	1.00	1.00

## Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

## Performances & Features



85%



ISO 5

ISO 14644-1



95% RH<sup>1</sup>



2.4 Kg/m² (15mm)



<sup>1</sup>Except 5177M & 5178M (70% RH)

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 169.9.05.25