





Aruba Max

Aruba Max with its microperforated, finely sanded surface, offers improved levels of sound absorption and sound attenuation, making it a great choice for classrooms and other areas requiring Class C sound absorption.

Key Features

- Improved aesthetics with discreet perforations, a smoother finish and a class-leading, fully painted whiteness
- Balanced acoustical absorption performance of 0.65 α_w and sound attenuation of 35dB
- Fully painted, reinforced edges for a more robust tile and greater durability
- Easy to handle and re-engineered for a better, easier fit
- Ideal for classroom and general teaching conditions



Edge Detail	Board		Tegular24		Tegular15																									
																														
Thickness (mm)	18		18		18																									
Modules (mm)	600 x 600 5471M 1200 x 600 5472M		600 x 600 5473M		600 x 600 5475M																									
Suspension Systems	Gridline 24 Butt Cut / Joggled		Gridline 24 Butt Cut / Joggled		Gridline 15 Butt Cut / Joggled Gridline 15 Shadow																									
Colour	Global White																													
Sustainability	 46   A  EN 13964 / E1 																													
Acoustics	 EN ISO 354 & EN ISO 11654  EN ISO 10848-2 & EN ISO 717-1  EN ISO 140-3 & EN ISO 717-1 Hz α_p <table><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>R_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr><tr><td>Board, Tegular24, Tegular15</td><td>0.65</td><td>35 dB</td><td>17 dB</td><td>C</td><td>0.60</td><td>0.35</td><td>0.45</td><td>0.60</td><td>0.65</td><td>0.70</td><td>0.65</td></tr></table>							α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000	Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65
	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000																			
Board, Tegular24, Tegular15	0.65	35 dB	17 dB	C	0.60	0.35	0.45	0.60	0.65	0.70	0.65																			
Fire Reaction	 A2-s1, d0 EN 13501-1																													
Performances & Features	 85%  95% RH   Lifetime Guarantee 30 Year System Guarantee  4.3 Kg/m²   BIM READY																													

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 134.6.05.25