




## Oplia

Oplia is a smooth laminated finish providing balanced acoustic performance combining both sound absorption and sound attenuation.

## Key Features

- Winning balance of sound attenuation and absorption
- Enhanced product durability
- High light reflectance: 86%
- ISO 5 / A+
- Ideal for open plan offices, board rooms, SEN schools and libraries



Edge Detail	Board	Tegular24	Tegular15
Thickness (mm)	17	17	17
Modules (mm)	600 x 600 ..... 2801M 1200 x 600 ..... 2802M Triangle Tile 1200 x 1200 x 1200 . BPTT2802M	600 x 600 ..... 2803M	600 x 600 ..... 2805M
Suspension Systems	Gridline 24 Butt Cut / Joggled	Gridline 24 Butt Cut / Joggled	Gridline 15 Butt Cut/ Joggled Gridline 15 Shadow

Colour Global White

## Sustainability



80



A+



EN 13964 / E1



## Acoustics



EN ISO 354  
& EN ISO 11654



EN ISO 10848-2  
& EN ISO 717-1



EN ISO 140-3  
& EN ISO 717-1

Results based on Global White tiles

	$\alpha_w$	Dnfw	R <sub>w</sub>	Class	NRC	Hz $\alpha_p$						
						125	250	500	1000	2000	4000	
Board, Tegular24, Tegular15	0.65(H)	37 dB	20 dB	C	0.65	0.55	0.50	0.55	0.75	0.85	0.85	
Triangle	0.90	–	–	A	0.90	0.65	0.80	0.85	0.90	1.00	1.00	

## Fire Reaction



Euroclass A2-s1, d0  
EN 13501-1

## Performances & Features



86%



95% RH



4.6 Kg/m²



ISO 5



ISO 14644-1



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 168.6.08.25