



Prestige dB

Prestige dB offers a finely textured and durable surface with a brighter 'blue-white' colour for excellent light reflectance. With high sound attenuation performance, it improves privacy between adjacent spaces.




Key Features

- Reduces the need for sound barriers in closed offices
- Very high light reflectance: 87%
- Better finish and more durable edges
- 30 year system guarantee
- Ideal for individual / private offices and boardrooms



Order a sample



Edge Detail	Board	Tegular24	Tegular15																																																			
																																																						
Thickness (mm)	19	19	19																																																			
Modules (mm)	600 x 600 7688M 1200 x 600 7690M	600 x 600 7695M	600 x 600 7697M																																																			
Suspension Systems	Gridline 24 Butt Cut & Joggled Gridline 24 Corrosive Resistant Gridline 24 Clean	Gridline 24 Butt Cut & Joggled Gridline 24 Corrosive Resistant Gridline 24 Clean	Gridline 15 Butt Cut & Joggled Gridline 15 Shadow																																																			
Colour	Global White																																																					
Sustainability	 39		 A+  EN 13964 / E1																																																			
Acoustics	 EN ISO 354 & EN ISO 11654  EN ISO 10848-2 & EN ISO 717-1  EN ISO 140-3 & EN ISO 717-1 <table><thead><tr><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>R_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th><th colspan="2">Hz α_p</th></tr></thead><tbody><tr><td>Board, Tegular24, Tegular15</td><td>0.60(H)</td><td>41 dB</td><td>21 dB</td><td>C</td><td>0.65</td><td>0.25</td><td>0.35</td><td>0.55</td><td>0.80</td><td>0.90</td><td>0.95</td><td colspan="2"></td></tr></tbody></table>																											α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000	Hz α_p		Board, Tegular24, Tegular15	0.60(H)	41 dB	21 dB	C	0.65	0.25	0.35	0.55	0.80	0.90	0.95		
	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000	Hz α_p																																										
Board, Tegular24, Tegular15	0.60(H)	41 dB	21 dB	C	0.65	0.25	0.35	0.55	0.80	0.90	0.95																																											
Fire Reaction	 Euroclass A2-s1, d0 EN 13501-1																																																					
Performances & Features	 87%	 7.6 Kg/m²				 30 Year System Guarantee	 95% RH	 ISO 5 ISO 14644-1			 BIM READY																																											

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 157.7.09.25