




VynaBoard Vinyl Gypsum Tile














This durable gypsum ceiling tile has a dappled vinyl face and foil backing. The vinyl face makes it easy to wipe down making it ideal for areas where regular cleaning is required such as commercial kitchens and canteens.

VynaBoard

Key Features

- // Durable gypsum board ceiling tile
- // Easy to clean vinyl face finish
- // Ideal for use in areas that are required to be cleaned down regularly
- // Foil backed to help reflect heat and resist moisture in the ceiling void
- // Only available in white



Edge Detail	Board																																			
																																				
Thickness (mm)	8																																			
Modules (mm)	600 x 600 8020M 1200 x 600 8021M																																			
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant																																			
Colour	White																																			
Sustainability	<div></div> <div>EN 13964 / E1</div>																																			
Acoustics	<div><div><div>EN ISO 354 & EN ISO 11654</div></div><div><div>EN ISO 10848-2 & EN ISO 717-1</div></div><div><div>EN ISO 140-3 & EN ISO 717-1</div></div></div> <table><thead><tr><th></th><th>α_w</th><th>D_{nfw}</th><th>R_w</th><th>Class</th><th>NRC</th><th>125</th><th>250</th><th>500</th><th>1000</th><th>2000</th><th>4000</th></tr></thead><tbody><tr><td>VynaBoard</td><td>0.10(L)</td><td>34 dB</td><td>15 dB</td><td>–</td><td>0.10</td><td>0.25</td><td>0.20</td><td>0.10</td><td>0.05</td><td>0.10</td><td>0.10</td></tr></tbody></table>													α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000	VynaBoard	0.10(L)	34 dB	15 dB	–	0.10	0.25	0.20	0.10	0.05	0.10	0.10
	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000																									
VynaBoard	0.10(L)	34 dB	15 dB	–	0.10	0.25	0.20	0.10	0.05	0.10	0.10																									
Fire Reaction	<div><div>A2-s1, d0 EN 13501-1</div></div>																																			
Performances & Features	<div><div><div>76%</div></div><div><div>95% RH</div></div><div><div>30 Year System Guarantee</div></div></div> <div><div><div>6.5 Kg/m²</div></div><div></div><div><div>BIM READY</div></div></div>																																			

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 225.2.07.25