


Oplia hA dB

Oplia hA dB combines the smooth Oplia laminated appearance with the highest levels of sound absorption and sound attenuation in one tile, providing a solution for flexible working spaces.

Key Features

- Opia hA dB includes a large selection of sizes and quality edge details enhancing durability
- The best acoustical combination of high sound absorption and high sound attenuation properties
- Ideal for open plan offices, board rooms, SEN schools and libraries



| Edge Detail | Board | | Tegular24 | | Tegular15 | | | | | | | | |
|-------------------------|---|------------|-----------------------------------|---------------------------------|--|-----|------|------|---------------|------|------|------|------|
| | | | | | | | | | | | | | |
| Thickness (mm) | 40 | | 40 | | 40 | | | | | | | | |
| Modules (mm) | 600 x 600 5044M 1200 x 600 5045M | | 600 x 600 5104M | | 600 x 600 5114M | | | | | | | | |
| Suspension Systems | Gridline 24 Butt Cut / Joggled | | Gridline 24 Butt Cut / Joggled | | Gridline 15 Butt Cut / Joggled Gridline 24 Shadow | | | | | | | | |
| Sustainability | 44 | | A+ | EN 13964 / E1 | | | | | | | | | |
| Colour | Global white | | | | | | | | | | | | |
| Acoustics | EN ISO 354 & EN ISO 11654 | | EN ISO 10848-2 & EN ISO 717-1 | EN ISO 140-3 & EN ISO 717-1 | Hz α_p | | | | | | | | |
| | | α_w | D _{nfw} | R _w | Class | NRC | 125 | 250 | 500 | 1000 | 2000 | 4000 | |
| | Board, Tegular24, Tegular15 | | 0.90 | 40 dB | 20 dB | A | 0.85 | 0.35 | 0.60 | 0.90 | 1.00 | 1.00 | 1.00 |
| Fire Reaction | Euroclass A2-s1, d0 EN 13501-1 | | | | | | | | | | | | |
| Performances & Features | 85% | 95% RH | ISO 5 | 30 Year System Guarantee | | | | | | | | | |
| | 6.2 Kg/m ² | | ISO 14644-1 | | | | | | BIM READY | | | | |

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 172.6.05.25