



Acousta Integra, Conceal & SL2 edge

Acousta has a fine textured surface and offers Class A sound absorption.

Key Features

- Excellent sound absorption: up to 1.00 α_w
- High light reflectance: 86%
- Excellent mechanical strength
(fibreglass fleece at the back)
- Ideal for open spaces, call centres and libraries

Edge Detail	Integra		Conceal		SL2		SL2	
Thickness (mm)	22		20		20		30	
Modules (mm)	600 x 6002288M 1200 x 6002289M		600 x 6002290M 1200 x 6002291M		1500 x 3002292M 1800 x 3002293M		2400 x 3002294M	
Suspension Systems	Gridline 24 Butt Cut/ Joggled		Gridline System Z L-Bar		Gridline System Z T-Bar Gridline System Z Z-Bar		Gridline System Z T-Bar Gridline System Z Z-Bar	
Colour	Global White							
Sustainability	80EN 13964 / E1							
Acoustics	α_w D_{nfw} R_w Class NRC 125 250 500 1000 2000 4000 Hz α_p Integra, Conceal, SL21.0028 dB13 dBA0.950.600.900.950.951.001.00							
Fire Reaction	Euroclass A2-s2,d0 EN 13501-1							
Performances & Features	86% 95% RH 3.6 Kg/m² (Integra) 3.1 Kg/m² (Conceal) 2.9 Kg/m² (SL2 1500) 2.8 Kg/m² (SL2 1800) 4.2 Kg/m² (SL2 2400)							

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email enquiries@zentia.com

TDS 258.1.01.26