



Mezzguard

Combine outstanding fire resistance with high light reflectance and balanced acoustical performance.




Key Features

- // Engineered for excellent fire resistance performance tested to EN 1365-2:
 - REI30 (30 minutes) with mezzanine floor
 - REI60 (60 minutes) with a timber floor
 Contact ZTS for details of test build up
- // Finely sanded surface texture with small pin holes for well-balanced acoustical performance
- // With high light reflectance, these white tiles bounce natural light around a space and reducing reliance on artificial light



Edge Detail Board



Thickness (mm)	16
Modules (mm)	600 x 600 2620M 1200 x 600 3066M
Suspension Systems	Gridline 24 Butt Cut / Joggled
Colour	Global White

Sustainability

52

Acoustics



	Hz α_p										
	α_w	D_{nfw}	R_w	Class	NRC	125	250	500	1000	2000	4000
Board (16mm)	0.65	34 dB	18 dB	C	0.60	0.40	0.45	0.60	0.70	0.65	0.60

Fire Reaction



Euroclass A2-s1, d0
EN 13501-1

Performances & Features



84%



5.1 Kg/m²



95% RH



Wipeable with a moist cloth



Washable with a sponge dampened in water containing mild soap or diluted detergent



If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email info@zentia.com

TDS 080.4.02.26