

## **Key Features**

- Suitable for high pressure water cleaning
- $\prime\prime$  Excellent sound absorption 0.95  $\mathbb{Q}_{\downarrow\prime}$
- ISO 4 with Clean Room grid
- // Ideal for commercial kitchens and healthcare environments



Edge Detail	Board								
	24								
Thickness (mm)	18								
Modules (mm)	600 x 600								
Suspension Systems	Gridline 24 Butt Cut / Joggled Gridline 24 Corrosive Resistant Prelude 24 Clean Room								
Colour	Global White								
Sustainability									
	20	Α	EN 13964 / E1						

**Acoustics** 



& EN ISO 354 & EN ISO 11654

	Hz α <sub>P</sub>								
	$a_{w}$	Class	NRC	125	250	500	1000	2000	4000
Board	0.95	Α	0.95	0.40	0.85	0.90	0.90	0.95	0.90

## **Fire Reaction**



Euroclass A2-s1, d0 EN 13501-1

## Performances & Features



82%



95% RH



ISO











.3 Kg/m²









<sup>&</sup>lt;sup>1</sup> The application must be in the form of a fan spray of 30° angle and not a high pressure 'cutting jet'.

The suggested minimum distance between the nozzle and the ceiling tile should not be less than 300 mm and the angle of projection should be 45°. Parafon Hygien should be installed with Gridline 24 Corrosive Resistant grid and be clipped for high pressure water cleaning. Cleaning recommended twice a year.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on 0800 371 849 or email enquiries@zentia.com

TDS 099.2.03.24

