



## Hygiene


Hygiene offers a Class A sound absorption, washability and hygiene performances.

## Key Features

- ✔ Suitable for high pressure water cleaning
- ✔ Excellent sound absorption 0.95  $\alpha_w$
- ✔ ISO 4 with Clean Room grid
- ✔ Ideal for commercial kitchens and healthcare environments



## Edge Detail Board




**Thickness (mm)** 18

**Modules (mm)** 600 x 600 ..... 9702M  
1200 x 600 ..... 9703M


**Suspension Systems** Gridline 24 Butt Cut / Joggled  
Gridline 24 Corrosive Resistant  
Prelude 24 Clean Room


**Colour** Global White

**Sustainability**




20






A



EN 13964 / E1

**Acoustics**



EN ISO 354  
& EN ISO 11654


	Hz $\alpha_p$								
	$\alpha_w$	Class	NRC	125	250	500	1000	2000	4000
Board	0.95	A	0.95	0.40	0.85	0.90	0.90	0.95	0.90

**Fire Reaction**



Euroclass A2-s1, d0  
EN 13501-1


**Performances & Features**



82%




95% RH



ISO 4






1




30 Year System Guarantee





1.3 Kg/m<sup>2</sup>





ISO 14644-1





BIM READY

<sup>1</sup> The application must be in the form of a fan spray of 30° angle and not a high pressure 'cutting jet'. The suggested minimum distance between the nozzle and the ceiling tile should not be less than 300 mm and the angle of projection should be 45°. HYGIENE should be installed with Gridline 24 Corrosive Resistant grid and be clipped for high pressure water cleaning. Cleaning recommended twice a year.

If you would like to order a sample or have any queries about this product please contact our Technical Sales Team on **0800 371 849** or email [enquiries@zentia.com](mailto:enquiries@zentia.com)

TDS 099.3.04.24